



UVG5 HEADLIGHT Compact, light and adjustable, frees your hands during inspections.

UVG3 and UVG5 make use of specialized filters that do not suffer from solarization. This means that the intensity level does not deteriorate over time and users do not need to replace filters. All units are available with a certificate of compliance for ASTM E3022-15.

# **UVG3** Midlight $\approx 8000 \, \mu W/cm^2$

COMPLIES WITH ASTM E3022-2015 Standard

### **UVG3** Floodlight $\approx 3~000~\mu W/cm^2$

COMPLIES WITH ASTM E3022-2015 Standard

COMPLIES WITH Airbus AITM6-1001 Testing Method

### **UVG5** Midlight $\approx 8000 \, \mu W/cm^2$

COMPLIES WITH ASTM E3022-2015 Standard

# **UVG5** Floodlight

 $\approx 3~000~\mu W/cm^2$ 

COMPLIES WITH ASTM E3022-2015 Standard

COMPLIES WITH Airbus AITM6-1001 Testing Method

#### **TESTED TO COMPLY WITH**

		Initial UV Intensity* (µw/cm²)	ASTM E3022-15 Standard	ROLLS-ROYCE RRES 90061 Specification	
GX SERIES – OVERHEAD LIGI	нт	( )		.,	
10000	GX Orion REMOTE	I 500 – 7 000	<b>√</b>		
	GX Orion UV & WH	≈ 7 000	✓		
	GX Orion <sup>UV</sup>	≈ 4 500	✓	<b>✓</b>	✓
	GX Orion PLC	I 500 – 7 000	✓		
BB SERIES – HANDHELD LIGHT					
	BB Helios	≈ 8 500	✓		
	BB Ikaros	≈ 4 000	✓	✓	<b>✓</b>
MB SERIES – HANDHELD LIG	HT				
	MB Hercules Ex	≈ 4 000	✓	✓	✓
	MB Zeus	≈ 4 000	<b>✓</b>		✓
	MB Hermes	≈ 4 000	<b>✓</b>	✓	✓
	MB Zeus with Athena	≈ 4 000	/		✓
	MB Hermes with Athena	≈ 4 000	✓	✓	✓
	MB Iris	≈ 4 000	/	<b>√</b>	<b>✓</b>
	MB Poseidon		В	lue Light (450 n	m)
UVG SERIES – FLASHLIGHT / HEADLIGHT					
	UVG3 MIDLIGHT	≈ 8 000	✓		
	UVG3 FLOODLIGHT	≈ 3 000	/		✓
	UVG5 MIDLIGHT	≈ 8 000	/		
	UVG5 FLOODLIGHT	≈ 3 000	/		<b>/</b>
	* As a disease of 20am (IE inches)				

<sup>\*</sup> At a distance of 38cm (15 inches)